

DH-NVR4216/4232-16P

16/32CH 1U 16PoE Network Video Recorder



Features

- > Up to 16/32 channel IP camera input
- > H.264/MJPEG dual codec decoding
- > Max 200Mbps incoming bandwidth
- > Up to 5Mp resolution preview&playback
- > HDMI/VGA simultaneous video output
- > 16 channel synchronous realtime playback, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.
- > ONVIF Version 2.4 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 2 USB(1 USB3.0)
- > Support IPC UPnP, 16PoE ports
- > Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS

DH-NVR4216/4232-16P


Technical Specifications

Model	DH-NVR4216-16P	DH-NVR4232-16P
System		
Main Processor	Dual-core embedded processor	
Operating System	Embedded LINUX	
Video& Audio		
IP Camera Input	16 channel	32 channel
Two-way Talk	1 channel Input, 1 channel Output, RCA	
Display		
Interface	1 HDMI, 1 VGA	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4/8/9/16	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Compression	H.264/MJPEG	
Resolution	5Mp(2560×1920)/4Mp(2560×1440)/3Mp(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1 (704×576/704×480)	
Record Rate	200Mbps	
Bit Rate	48~ 8192kbps	
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	4 channel	
Relay Output	2 channel	
Playback & Backup		
Sync Playback	1/4/8/16	1/4/8/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode	USB Device/Network/Internal SATA burner	
Network		
Ethernet	1 RJ-45 port (10/100/1000Mbps)	
PoE	16 ports (IEEE802.3at/af)	
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)	
Max. User Access	128 users	
Smart Phone	iPhone, iPad, Android	
Storage		

DH-NVR4216/4232-16P

Internal HDD	2 SATA ports, up to 8TB
Auxiliary Interface	
USB	2 ports (1 Rear USB3.0,1 Front USB2.0)
RS232	1 port, For PC communication&Keyboard
General	
Power Supply	Single, AC 100~240V, 47/63 Hz
Power Consumption	NVR: <30W(without HDD) PoE: Max 25.5W for single port, 130W in total
Working Environment	-10°C~+55°C / 10%~90%RH / 86~106kpa
Dimension (W×D×H)	1U, 375mm×327mm×53mm
Weight	2.5KG(without HDD)

System Connection



*Take NVR4216-16P as an example

Dahua Technology Co., Ltd.

1199'BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2015 Dahua Technology Co., Ltd.